

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

PCT / SE 2004 / 001437

REC'D 25 OCT 2004

WIPO

PCT

Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.


(71) Sökande Neural AB, Lund SE
Applicant (s)

(21) Patentansökningsnummer 0302676-2
Patent application number

(86) Ingivningsdatum 2003-10-09
Date of filing

Stockholm, 2004-10-12

För Patent- och registreringsverket
For the Patent- and Registration Office


Gunilla Larsson

Avgift
Fee

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

PATENT- OCH
REGISTRERINGSVERKET
SWEDEN

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 666 02 86
08-666 02 86

APPLICANT: NEURAL AB

TITLE: METHOD AND APPARATUS FOR HOLOGRAPHIC REFRACTOMETRY

5 AREA OF INVENTION

The present invention relates to a method and device for holographic refractometry useful for the comparison of refractive index between an object and a surrounding medium using digital holography.

10

PRIOR ART

A commonly known method for determination of refractive index of small inhomogenous, transparent objects is the method known as the Becke method. The Becke method involves placing the object in a medium having a known refractive index, for example a Refractive Index Liquid. The sample is arranged in a microscope and light is passed through the sample. The person using the microscope moves the focal plane upwards (or downwards). The Becke lines seem to move outwards or inwards relative to the contour of the object. The movement of the Becke lines is dependent on whether the refractive index of the object is lower or higher than the refractive index of the surrounding medium. By placing the object in several media having different refractive index and observing when the movement of the contour change direction as the focal plane is moved upwards, the refractive index of the object may be determined. Thus, the Becke method of determining refractive index of an object is an indirect method.

30 The Becke method involves that a person has to move the focal plane of the microscope by hand while observing the movement of the contours of the object. Thus, the method does not lend itself for automation. Moreover, the analysis has to be performed at site. Thus, it is not possible to make an image of the object and to analyze the image afterwards in another environment or at another time.

PPV 03-100941

Other methods of measuring refractive index are the phase contrast method and the oblique illumination method, see for example W. D. Nesse, "Introduction to optical Mineralogy", Oxford University Press, New York, second edition, 1991.

Refractometry has applications in different sciences. The index of refraction is material specific, which is useful in identification of different substances in a blend. In pharmacology, particle size characterization and distribution of chemical substances play an important role in research and manufacturing. In mineralogy, the index of refraction is an important parameter in classifying different minerals.

15 SUMMARY OF THE INVENTION

Accordingly, it is an objective of the invention to provide a method and a device that makes it possible to automate the process of measuring the refractive index of an object.

20 A second objective of the invention is to provide a method and device that enables remote analyzing of the refractive index of an object at any time after that an image of the object has been obtained.

These objectives are met with a method and device
25 for determining refractive index of an object compared to a refractive index of a surrounding medium, by exposing said sample to a laser object beam and letting the object beam interfere with a laser reference beam to obtain a hologram, analyzing the hologram for phase information, and
30 determining if the refractive index of the object is higher or lower than the refractive index of the surrounding medium based on said phase information. The method may be performed by a computer.

The method may be used for counting the number of
35 particles having a first refractive index and counting the

number of particles having a second refractive index in a specific area of said sample if the object has particles of a first substance having a first refractive index and a second substance having a second refractive index and a medium having a refractive index between said first and second refractive index. In this way the relationship between the substances may be calculated.

BRIEF DESCRIPTION OF THE DRAWINGS

Further objects, features and advantages of the invention will become apparent from the following description of several embodiments of the invention with reference to the drawings, in which:

Fig. 1 is a schematic diagram of an experimental setup for performing the method according to the invention.

Fig. 2 is a schematic diagram of an object comprising wave fronts moving beyond the object.

Fig. 3 is a schematic diagram showing a phase analysis of a hologram obtained of the object of Fig. 2.

Fig. 4 is a photograph showing a microscope view of a sample comprising objects according to the invention.

DETAILED DESCRIPTION OF EMBODIMENTS

Fig. 1 is a schematic diagram of an experimental setup of a Fourier holography equipment. The equipment comprises a JDS Uniphase 10 mW He-Ne laser 17 emitting light at the wavelength of 633 nm. The light passes a shutter 6, a first polarizer 5 and a second polarizer 4. By the polarizers, the intensity of the laser beam may be adjusted. Thence, the laser beam passes a first halfwave plate 3 and reaches a polarizing beam splitter 2 dividing the beam into a object beam 14 and a reference beam 15. The object beam 14 passes a second halfwave plate 7 and is diverted 90 degrees by a mirror 10. Thence, the object beam passes an Iris diaphragm 16 and reaches a beam splitter 9. The refer-

ence beam 15 is diverted by a mirror 1 towards the beam splitter 9 and passes a GRIN lens 11, which diverts the reference beam 15 as shown in the enlarged section of Fig. 1.

5 An object 12 is arranged close to the beam splitter 9. The laser beam passing through the object is collected by a sensor 8. The reference beam is diverted towards the sensor 8 by the beam splitter 9, whereby the sensor 8 comprehends the reference beam as originating from a virtual
10 point source 13 close to the object.

By means of the two halfwave plates, the intensity in the reference beam and the object beam may be controlled and at the same time keep the polarization of the fields linear.

15 The experimental digital holograpy setup implies a spherical reference point source close to the illuminated object. This gives approximately the same curvature of the reference field and the object field and hence low spatial frequencies of the hologram. To achieve a large numerical
20 aperture of the reference field and keep the point source close to the object, a 0.25 pitch GRIN lens is used to widen the reference beam. The GRIN lens has a numerical aperture of 0.37, a diameter of 1.0 mm and is placed in a holder close to the beam splitter. The reference point
25 source is thereby reflected by the beam splitter to the sensor. The arrangement with the beam splitter gives a virtual point source which can be placed close to the object.

In the experimental setup, it is not possible to measure the object field directly. Instead an approximation
30 of the object field and the reference field, i.e. a sampled version of the interference pattern, is measured by the sensor. The object field is used to determine an image of the object. The evaluation of the object field is performed in a computer by means of FFT (fast Fourier transforms).

The experimental setup described so far may be altered in different applications. For example, the Iris diaphragm 16 may be omitted as well as the members 3, 4, 5, 6 and/or 7. Mirrors 1 and 10 may be replaced by optical fibres, etc.

In the method according to the invention, it is possible to see completely transparent objects, such as biological specimens, without any preparation. To the contrary, in the prior art, specimens are routinely stained. This approach is unsatisfactory in many respects. The stain, for example, kills a specimen whose life processes may be under study.

In Fig. 2, a transparent object is shown. The object does not absorb any light, but the light that travels through the object will experience a difference in the optical path length. The wave front that emerges from the object will thus not be a plane wave, as it was when it entered the object. This distortion can be detected with holography as phase differences and for example be represented as a hue difference on a computer printout.

Fig. 3 shows a hologram print-out of the object according to Fig. 2, in which the different heights are displayed as different phases represented by different colors. Thus, the inner circle may be blue 41, the next ring 42 green, the following ring 43 yellow and the outer ring 44 red.

Fig. 4 is a phase image of lactose crystals mounted in a liquid with $n_m = 1.542$. The phase increases (decreases) when going from an object with higher (lower) refractive index to an object with lower (higher) refractive index. The photograph at the top is the unwrapped phase image and the photograph at the bottom is the re-wrapped phase image.

In the present invention, a single hologram is obtained. A hologram comprises information of several focal

planes. Consequently, it is possible to maintain the hologram and later analyze it according to the Becke method. The computer may be programmed to produce images of the crystals at different focal depth and the movement of the contours of the crystals may be visualized.

However, it is observed that a hologram comprises phase information. By programming the computer to indicate the phase of the laser light from the object, it is possible to generate an image, in which the phase is displayed, for example as different colors or hues.

It has been observed that the phase order is different depending on whether the object has a refractive index, which is larger or smaller than the surrounding liquid refractive index.

Thus, the index of refraction of an isotropic object can be determined with repeated measurement where the surrounding medium or liquid is changed until the phase order has been reversed. The index of refraction for the object is then between the indexes of refraction for the two liquids having different phase order.

Moreover, two different isotropic objects can be separated if the surrounding liquid is matched somewhere between the indexes of refraction for the two objects. With multiple measurements, three or more objects may be separated.

Anisotropic objects have different indexes of refraction in different directions. The co-polarized part of the scattered light from an anisotropic object seems to have been scattered by an isotropic object with an effective index of refraction n' . By multiple exposures of the same object with a step by step rotation of the polarization of the illuminating light, the smallest and the largest of the principal refractive indexes can be extracted. The anisotropic objects considered here are uniaxial, i.e. they have

one optical axis where the index of refraction varies with polarization.

Fig. 4 shows an object consisting of lactose crystals. These crystals are anisotropic and have different refraction indexes in different directions. These crystals are arranged in a liquid having a refractive index of 1.542, for example a Cargille Refractive Index Liquid that may be obtained with predefined refractive index. The wrapped phase image is improved by an approximation to a two-dimensional phase unwrapping algorithm, whereby large scale phase variation of the illuminated wave is removed. Finally, the unwrapped phase image may be re-wrapped to the range of -2π to $+2\pi$.

The image is calculated by a computer and may be displayed as different shades of gray or as colors. The computer may be programmed to determine the number of objects that have a refractive index larger than or smaller than the refractive index of the surrounding medium.

As appears from Fig. 4, some of the particles are white and some of the particles are black, indicating whether the refractive index of the relevant particle is above or below the refractive index of the surrounding medium.

For example, if the method is to be used for determining the relationship between the number of particles of two isotropic substances having different refractive index, a medium is used with a refractive index in between the refractive indexes of the substances. In the processed hologram, the substances will appear as particles having different gray shade compared to the surrounding medium, for example substantially white and substantially black particles. The computer may be programmed to count the number of particles of each type on a specific surface area of the sample. Thus, the relationship between the two substances may be fully automatically calculated by the computer.

REV 03.10.00H

The method according to the invention lends itself to automatization so that the control of the blend of particles of substances in a batch may be controlled continuously over time by arranging samples continuously and performing the method as described above. Up to now, there is no reliable real time method of making such measurements.

The invention has been described above with reference to a specific embodiment of the invention shown on the drawings. However, a skilled person reading this specification may realize other combinations of the different features indicated in the embodiment, and such other combinations are intended to be within the scope of the invention. The invention is only limited by the appended patent claims.

4
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

PPV 03.10.09

PATENT CLAIMS

1. Method of determining refractive index of an object compared to a refractive index of a surrounding medium, **characterized by**
 - exposing said sample to a laser object beam and letting the object beam interfere with a laser reference beam to obtain a hologram,
 - analyzing the hologram for phase information,
 - determining if the refractive index of the object is higher or lower than the refractive index of the surrounding medium based on said phase information.
2. The method as claimed in claim 1, **characterized** in that said analyzing and determination are performed by a computer.
3. The method as claimed in claim 1 or 2, **characterized by**
 - said object comprising particles of a first substance having a first refractive index and a second substance having a second refractive index and a medium having a refractive index between said first and second refractive index;
 - counting the number of particles having a first refractive index and counting the number of particles having a second refractive index in a specific area of said sample.
4. A device for determining refractive index of an object compared to a refractive index of a surrounding medium, **characterized by**
 - a laser source for exposing said sample to a laser object beam and letting the object beam interfere with a laser reference beam to obtain a hologram,
 - a computer for analyzing the hologram for phase information, and for determining if the refractive index of

the object is higher or lower than the refractive index of the surrounding medium based on said phase information.

5. The device as claimed in claim 4, **characterized** in that

5 said object comprising particles of a first substance having a first refractive index and a second substance having a second refractive index and a medium having a refractive index between said first and second refractive index; and

10 said computer is arranged to count the number of particles having a first refractive index and the number of particles having a second refractive index.

6. Computer program arranged on a tangible medium for execution on a computer for performing at least one of
15 the method steps of any one of claims 1 to 3.

7. Use of the method of any one of claims 1 to 3 for the separation of particles in a particle blend.

ABSTRACT

5 A method and device for determining refractive in-
dex of an object compared to a refractive index of a sur-
rounding medium. The object is exposed to a laser object
beam and a laser reference beam to obtain a hologram. The
hologram is analyzed for phase information, and based
thereon, it is determined if the refractive index of the
object is higher or lower than the refractive index of the
10 surrounding medium.

(Figure for publication: Fig. 1)

031006